



# PRODUCT DATA



## 600GL Coatings Remover (Formerly SOY•Gel™ Paint and Urethane Remover)

Franmar's most-asked-for product, **600GL**, continues to impress contractors with its ease of use and powerful removal properties. With three times the coverage rate of traditional petroleum removers, **600GL** effectively removes multiple layers of topical sealers, acrylics, enamels, urethanes, latex, some epoxies, and other single-component coatings. Made with soybeans, **600GL** is a safe, low-odor, non-caustic, green coating remover.

As a leading innovator in green cleaning products, Franmar Chemical, Inc. introduced **600GL** as a soy based paint remover, and changed the industry. **600GL** is 100% biodegradable, practically odorless, and is safe for your hands, your work, and your customers.

### Coverage:

Coverage per square foot varies depending on type and age of coating, number of layers and method of application.

**Horizontal:** Average coverage is 125 sq ft per gallon (max 200 sq ft per gallon)

**Vertical:** Average coverage is 75 sq ft per gallon

### Test Area:

Due to variances in surfaces and conditions, always test in a small, inconspicuous area before using on complete project.

### Application:

Apply a thick layer of **600GL** by pouring, brushing, squeegee, or commercial airless sprayer. Applying too thin will cause **600GL** to dry out before removal is complete. Use a scraper to check if the coating is softened down to the surface. If not, wait longer and recheck. When the coating is completely softened, remove with a scraper.

### Clean Up:

Use **BLUE BEAR 700DG Degreaser** or water and a scrub brush, mop, or power washer to clean remaining thin residue. Remove excess coating(s) and **600GL** before using a power washer for final cleaning. Allow surface to dry before further preparations.

### Usage Tips from the Pros:

- For large application areas, use a professional airless sprayer or a 4-stage HVLP sprayer.
- For tough coatings or numerous layers, use a notched 1/2" squeegee or 1/4" gauge rake. Square footage will be greatly reduced.
- When used outdoors, cover with a 2mil or thicker plastic to help keep **600GL** wet and working.

**Biodegradable:** Meets or exceeds ASTM standards

**Precautions:** Concrete surfaces may darken with use of **600GL**. Protect plants and vegetation with a plastic drop cloth. Always use care to prevent overspray from getting on surfaces other than the one being prepped or cleaned.

**Warnings:** May cause skin irritation. May cause eye irritation. May cause respiratory irritation or may cause drowsiness and dizziness. May be harmful if swallowed. This product contains a chemical known to the state of California to cause birth defects or other reproductive harm. Keep out of reach of children.

**Flash Point** Above 200°F (93.3°C)

**pH Level** 8.1 pH of 1/10 wt/wt solution in soft water

**VOC (Volatile Organic Compounds)** 49%, 4.249 lb/g, 509 g/l  
California and OTC Compliant

**Ingredients:** N-Methyl Pyrrolidone, Dibasic Ester LVP, Soy Ester, Proprietary Thickening and Surfactant Blend

**Safe for Use On:** Concrete, masonry, wood, and metal

**Do Not Use On:** PVC, drywall, limestone, plastic, veneer, terrazzo tile, or rubber

### NON-EMERGENCY

Call: 800.538.5069

[www.franmar.com](http://www.franmar.com)

### CHEMICAL EMERGENCY:

Spill, Leak, Fire, Exposure, or Accident

Call CHEMTREC Day or Night

USA and Canada: 800.242.9300

CCN717946 or +1 703.527.3887

(Collect Calls Accepted)



PO Box 5565

Bloomington IL 61702

Copyright 2014

Rev. 1/22/2015